

# HOTRONIC® FOOTWARMER m SERIES

## PRODUCT SPECIFICATIONS CHART 09/10

<b>BATTERY PACK</b>		<b>m4</b>	<b>m3</b>
Weight (with Wire Clip)		6.2 ounces	4.8 ounces
Weight (withOUT Wire Clip)		5.8 ounces	4.4 ounces
Height		71 mm	71 mm
Width		64 - 66 mm	50 - 52 mm
Depth (with Wire Clip)		34 mm	34 mm
Depth (withOUT Wire Clip)		28 mm	28 mm
Cell Count / Type / Capacity		4 cells / NiMH / 2000 mAh	3 cells / NiMH / 2000 mAh
Battery Pack Voltage		4.8V (nominal)	3.6V (nominal)
<b>Temperature &amp; Duration Ranges</b>		<b>m4</b>	<b>m3</b>
<i>Setting</i>	<i>Temperature Range</i>	<i>Duration Range</i>	<i>Duration Range</i>
1	28 - 32 °C / 83 - 89 °F	19 - 21 h	15 - 17 h
2	36 - 41 °C / 96 - 106 °F	7 - 9 h	5.5 - 7 h
3	40 - 47 °C / 105 - 116 °F	5 - 6.5 h	3.5 - 5 h
4	57 - 62 °C / 135 - 144 °F	2.5 - 3.75 h	2 - 3 h
<b>RECHARGER</b>			
Voltage Input Range		100 - 240VAC, 50/60Hz, 0.43A	
Voltage Output Range		4.2 / 5.6VDC, 800mA x2 5.6VDC for 4.8V Battery Pack m4 4.2VDC for 3.6V Battery Pack m3	
Base Unit Dimensions (withOUT Plug Adapter)		45 mm X 88 mm X 29 mm	
Power Cord(s) Length (Base Unit to Plug End)		157.3 cm	
Weight (withOUT Plug Adapter)		4.8 ounces	
Weight (with Plug Adapter 120V)		5.3 ounces	
Weight (with Plug Adapter 240V)		5.6 ounces	
<b>HEATING ELEMENT</b>			
Oval Disc Dimensions		55 mm X 6 mm	
Oval Disc Thickness (with Adhesive and Cover)		< = 0.5 mm	
Oval Disc Thickness (with Surface Mount and Power Cord)		< = 1.5 mm	
Power Cord (width x thickness x length)		10.5 mm X 1.2 mm X 650 mm	
Plug (height x width x depth) (with Stress Relief)		50 mm X 17 mm X 7 mm	